# storbyte

### Model: SBS-460

#### **Key Features:**

- 4U Storage Server Array with 60 Hot-Swappable Drive Bays (Hybrid SSD and HDD Compatible)
- Up to 1.2PB RAW Storage Capacity at over 12GB/s Bandwidth
- Utilizes Enterprise Grade SSD, HDD, or a Hybrid Blend of both storage drive technologies
- Hardware Defined Storage for Future Proof Upgrades and Convenience

## **SPECIFICATIONS:**

Processor	Dual Intel® Xeon® SP Skylake CPUs with processor core count options per application	Supported File Systems	Storbyte Javelin, IBM GPFS, ZFS, LUSTRE, CEPH, GLUSTER, EOFS, QUOBYTE, StorONE, Windows 208 & 2012 R2, RHEL 6.5, SLES 11 SP3, VMWare
Throughput	12.8 GB/s bandwidth		ESXi 5.5, FreeBSD 9.2 Centos 6.5 and many others!
RAM Memory	8x DIMMs DDR4 RDIMM/RDIMM	Front Panel	Power On/OFF with LED, reset Switch, NMI switch, Locate Switch with LED, 2xLAN LED, Warning LED
Expansion Slots	Support up to total 6 PCIe slots; 3 PCIe3 x8; 1 PCIe3 x16, 1 PCIe3 x4, 1 PCIe2 x4	Rear I/O	2x USB 2.0 ports, 1x USB 3.0 ports, 1x VGA port, 1x COM port, 1 TPM Header, 2x GbE ports
Architecture	Two 48 port SAS Expander 6 SFF8643 24 port SAS To HBA/RAID	Fan Cooling	5x 97mm Enterprise Grade Exhaust Blower
		Other Features	Patented Tool-Less & Tray-Less Storage Bay Design
Drive Support	60x 3.5" SAS/SATA Storage Drives (Hot-Swap) 2x 2.5" 7mm OS Storage Drives (Internal) 4x U.2 NVMe Storage Drives (Optional)	Weight	Gross: 69 KG/152 LBS; Net: 60 KG/132 LBS
		Dimension	System: 36.5" x 19" x 7" (LxWxH)
Network	Dual GbE ports, 1x GbE dediated for IPMI		Packaging: 47.6" x 24.8" x 13.6" (LxWxH)
Power Supply	PSU REDUNDANCY OPTIONS INCLUDES: 2 +2 1600W (4@800W each) AC/DC redundant 1	Design/Assembled	Washington DC / USA
	+1 1600W (2@1600W each) AC/DC redundant 2+1 1600W (3@800W each) AC/DC redundant or optional DC input available upon request	Environmental	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
Supports Legacy Systems	Open Systems Architecture Interoperable Open Protocol Compliant	Compliance	CE, FCC Class A, RoHS 6/6 compliant

## **SPECIFICATION NUMBER:**

**SBS-460** 

STORBYTE 4U STORAGE ARRAY WITH 60x ENTERPRISE GRADE DRIVE BAYS



- Data Center/ Cloud & Virtualization
- Big Data Clustered Storage
- Enterprise VDI Scaleout ServersHadoop and Scale Out storage

WWW.STORBYTE.COM | INFO@STORBYTE.COM | Toll Free: 1-877-2-STORBYTE (1-877-278-6729) | Office: 202-505-5320 | Fax: 202-505-5319

Specifications are subject to change. Please verify with sales representative for latest revision.

Storbyte and the Storbyte logo are registered trademarks of Storbyte, Inc. All other trademarks are property of their respective owners.